



...competitive technologies
with compelling value

Rack Mountable High Velocity Triple Fan Blowers

Product Description

The CT-FANRK-B is a rack mountable ventilation system that incorporates 3 individual fans in a 3-rack space (5.25") housing. A single two-prong AC plug is attached to all three fans to minimize the number of outlets needed. The fans are reversible to provide either exhaust or air intake.

The CT-FANRK-B operates with a very low amount of noise while maintaining a high volume of air movement. Each individual fan is capable of moving up to 92 cubic feet of air per minute for a combined flow of up to 276 CFM.

Application

The CT-FANRK-B is highly recommended above any chassis mounted modulator set. One CT-FANRK-B should be used with each bank of modulators even when the chassis is not completely full.

Specifications

Fan number	3
AC input	110/120VAC
Rated power	17W
Operation voltage	90VAC~130VAC

Power cord length	3'
Maximum Capacity	276 CFM (Cubic Feet Per Minute)
Operating temperature	14°F - +176°F
Weight	4.85 Lbs.
Dimensions	19" W x 5.25" H x 3.8" D

Ordering Information

CT-FANRK-B	Rack mountable, horizontal high velocity triple fan blower
CT-FANRK-B-PLUS	Rack mountable, horizontal high velocity triple fan blower, all metal unit

Features

- Three individual fans in 1.75" of rack space (1 rack space)
- Fans draw air in through the bottom and out the front
- Low noise, High volume
- Black powder coat finish
- All three fans are tied into 1 power source, power adapter included



CT-FAN3-RK-B

Product Description

The CT-FAN3-RK-B is a rack mountable ventilation system that incorporates 3 individual fans in a single rack space (1.75") housing. A single power output is attached to all three fans to minimize the number of outlets needed. The fans draw air in from the bottom of the chassis and out through the front of the chassis.

The CT-FAN3-RK-B operates with a very low amount of noise while maintaining a high volume of air movement. Each individual fan rotates at 2300 revolutions per minute (+/- 10%) for a combined 6,900 RPM of air flow.

The CT-FAN3-RK-B is highly recommended above any chassis mounted modulator set. One CT-FAN3-RK-B should be used with each bank of modulators even when the chassis is not completely full.

Specifications

Fan number	3
Power supply	External AC to DC adapter
AC input	100-240V, 50-60Hz, 1A
DC Output	12V, 3000mA, 36W
Power cord length	6'

Speed (RPM)	2300+/-10%
Operating temperature	14°F - +176°F
CT-FAN3-RK-B Weight	5.0 Lbs.
CT-FAN3-QTRK-B Weight	13.25 Lbs.
CT-FAN3-RK-B Dimensions	19" W x 1.75" H x 5.0" D
CT-FAN3-QTRK-B Dimensions	19" W x 1.75" H x 14.0" D

Ordering Information

CT-FAN3-RK-B	Rack mountable, vertical high velocity triple fan blower
CT-FAN3-QTRK-B	Rack mountable, vertical high velocity triple fan blower, ultra-quiet model

Email: info@solidsignal.com Web: www.solidsignal.com