NF141208VP



14x12x8 Vented Fiberglass Weatherproof NEMA Enclosure with Blank Aluminum Equipment Mounting Plate



Features

- (2) 4 inch Vents with Rain Shields and Screens
- Includes Easy to Drill Blank Aluminum Equipment Mounting Plate
- Extended Lid for Increased Equipment Clearance
- RF Transparent Enclosure
- Stainless Steel Hinge and Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA Type 3R, 3RX / IP24 Rated
- Includes Stainless Steel Mounting Feet
- Optional Pole Mounting Kit Available



Description

The **Altelix NF141208VP** features two 4 inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting equipment from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

Aluminum Equipment Plate - This enclosure features an easy to drill aluminum equipment mounting plate. The enclosure and plate can be drilled and modified by the installer to suit unique site requirements.

Extreme Protection Built to Last - This rugged JIC style NEMA box is molded from durable UV stable and corrosion resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. The FRP material is dent-proof, non-conductive and RF transparent for compatibility with wireless equipment. It can be easily drilled and modified by the installer as needed. The enclosure features a gasketed door with stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. The generous size of this enclosure and the extended lid accommodate a wide range of equipment.

Cable Glands - The enclosure features our unique PG-16 cable glands with a closed inner seal. They are installed in the open ports to maintain the NEMA rating of the enclosure when not in use. When required for use, simply punch a hole through the inner membrane, run your cables and tighten for a water-tight seal.

Mounting - Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Gray
Outer Dimensions	15.7 x 13.8 x 10.1 Inches (401 x 352 x 258 mm)
Inner Dimensions*	13.0 x 11.0 x 7.5 Inches (330 x 279 x 190 mm)
Mounting Plate Material	0.10 inch (2.5 mm) Aluminum
Mounting Plate Dimensions	10.9 x 12.8 inch (267 x 324 mm)
Weight	10.9 lbs. (5.0 kg)
Ratings	NEMA 3R, 3RX / IP24
Flame Rating	UL94-5V
Industry Certifications	CE

^{*}Interior dimensions represent maximum space available for equipment.