



## Features

- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with a Pre-Wired 120VAC Power Plug
- Prewired 5 Foot Power Cord
- (2) 2¼" Vents and Thermostat Controlled Cooling Fan
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Extra Deep Gasketed Lid with Dual Latches, Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Grommets and Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available

## Description

---

The **Altelix NP120907VFA1C-0C** features two 2¼" inch air vents and a thermostat-controlled cooling fan. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries. It features an extra deep lid providing additional depth.

**Construction and Features** - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. Integrated mounting feet simplify installation.

**Cooling Fan Ventilation** - The NP120907VFA1C-0C features two 2¼" inch air vents and a thermostat-controlled cooling fan. The low noise, high airflow fan helps maintain lower internal temperatures. Rain shrouds on the front door keep rainwater from entering the enclosure.

**120VAC Power** - This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a pre-wired 3-prong 120VAC power plug. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required.

**Complete with Cable Grommets, Cable Glands and Wire Management Accessories** - For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## Specifications

---

<b>Material</b>	Polycarbonate + ABS
<b>Color</b>	Gray
<b>Cooling Fan Turn-On Temperature</b>	100°F (38°C)
<b>Cooling Fan Turn-Off Temperature</b>	79°F (26°C)
<b>Voltage / Max Load</b>	120VAC / 10A @ 120VAC
<b>Outer Dimensions</b> (Height x Width x Depth)	13.1 x 10.2 x 8.0 Inches (334 x 259 x 204 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	8.5 x 7.5 x 4.7 Inches (216 x 190 x 119 mm)
<b>Mounting Plate Material</b>	0.06 In. (1.5 mm) Aluminum
<b>Weight</b>	4.5 lbs. (1.5 kg)
<b>Power Cord Length</b>	5 Feet (1.5m)
<b>Ratings</b>	Meets NEMA 3R, 3RX and IP24
<b>Flame Rating</b>	Meets UL94-V0

\*Interior dimensions represent maximum space available for equipment.