



Features

- (2) 3" Vents with Rain Shields
- Features a 1/4" Thick No-Drill Non-Metallic PVC Equipment Mounting Plate
- Pre-wired 120VAC Power Outlet
- Pre-wired 5 Foot Power Cord
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available

Description

The **Altelix NP131004VMA1C** features two 3" air vents covered by rain shields, with cleanable screens. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

Construction and Features - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 3R, 3RX IP24.

Power - This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a non-metallic PVC plate with a 120VAC power outlet. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. Cable glands on the enclosure allows cables to be connected to internal devices.

RF Transparent Design - The NP131004VMA1C is ideal for WiFi applications. The non-metallic design of both the enclosure and equipment mounting plate will not interfere the radio's operation. In addition, mounting radios to the PVC equipment mounting plate can be done simply by using self-tapping screws. The size of this enclosure will fit a wide range of popular wireless points on the market.

Complete with Cable Glands and Wire Management Accessories - This enclosure includes 3 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray
Voltage / Max Load	120VAC / 10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	13.7 x 10.8 x 5.4 Inches (348 x 274 x 136 mm)
Inner Dimensions* (Height x Width x Depth)	7.0 x 7.8 x 3.3 Inches (178 x 197 x 82 mm)
Mounting Plate Material	0.25 in. (6.4 mm) PVC
Weight	3.2 lbs. (1.4 kg)
Power Cord Length	5 Feet (1.5m)
Ratings	Meets or Exceeds NEMA 3R, 3RX and IP24
Flame Rating	Meets UL94-V0
Included Cable Glands	(3) M24 x 1.5

*Interior dimensions represent maximum space available for equipment. See drawing for additional details.