

14x11x5 Polycarbonate + ABS Vented Indoor / Outdoor RF Transparent Enclosure with PVC Non-Metallic Equipment Mounting Plate, 120VAC Outlets & Power Cord



## Features

- Dual 3" Vents with Rain Shields to Expel Heat
- ABS + Polycarbonate Construction
- Gasketed Lid with Tamper-Proof Locking Screw
- Dual Door Latches
- Features a No-Drill PVC Non-Metallic Equipment Mounting Plate
- (2) Pre-Wired 120VAC Outlets
- Pre-wired 5 Foot Power Cord
- NEMA Type 3R, 3RX / IP24 Rated
- Includes Wall Mount Hardware and Cable Grommets
- Optional Pole Mount Kits Available

## Description

---

The **Altelix NP141105VMA1C** NEMA enclosure is simple to install because no wiring is required. Simply mount the enclosure and plug the pre-wired 5 foot power cord into a nearby outlet. The non-metallic equipment mounting plate features two pre-wired 120VAC power outlets for your equipment. A cable grommet on the enclosure allows cables to be connected to internal devices.

**Get your project up and running quickly** and transition to hard-wired later if needed. The power cord can be easily removed, and the power receptacle hard wired by an electrician or qualified installer.

### Polycarbonate + ABS Protection Built to Last

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for a padlock.

Knock-out holes are provided on the top and bottom.

### Ventilation

The NP141105VMA1C features two 3" vents. Rain shrouds on the front door keep rain water from entering the enclosure.

### RF Transparent Design

The NP141105VMA1C is ideal for WiFi applications. The non-metallic design of both the enclosure and equipment mounting plate will not interfere the radio's operation. In addition, mounting radios to the PVC equipment mounting plate can be done simply by using self-tapping screws. The size of this enclosure will fit a wide range of popular wireless points on the market.

## Specifications

---

<b>Material</b>	PC+ABS Polycarbonate / ABS Blend
<b>Available Colors</b>	Gray and Black
<b>Voltage / Max Load</b>	120VAC / 10A @ 120V
<b>Outer Dimensions</b> (Height x Width x Depth)	13.4 x 11.5 x 6.3 Inches (340 x 293 x 160 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	9.5 x 8.0 x 3.7 Inches (241 x 203 x 94 mm)
<b>Mounting Plate Material</b>	0.25 in (6.4 mm) PVC
<b>Mounting Plate Dimensions</b>	11.7 x 9.0 in. (298 x 230 mm)
<b>Weight</b>	4.7 lbs. (2.1 kg)
<b>Power Cord Length</b>	5 Feet (1.5m)
<b>Ratings</b>	NEMA Type 3R, 3RX / IP24
<b>Flame Rating</b>	Meets UL94-V0
<b>Knockout Sizes (Diameter)</b>	(4) 0.62 in. (16 mm) (4) 0.78 in. (20 mm) (4) 1.30 in. (33 mm)

\*Interior dimensions represent maximum space available for equipment.