NP151005VA1C-0C

15x10x5 Vented Polycarbonate + ABS Weatherproof Enclosure with Equipment Mounting Plate, 120VAC 3-Prong Power Plug & Power Cord



Features

- (2) 3" Vents with Rain Shields and Screens
- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with pre-wired 120VAC 3-Prong Power Plug
- Pre-wired 5 Foot Power Cord
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps

Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2021 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.

NP151005VA1C-0C

Description

The **Altelix NP151005VA1C-0C** features two 3" inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

Construction and Features - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 3R, 3RX and IP24.

120VAC Power - This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a pre-wired 120VAC 3-prong power plug. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. A cable gland on the enclosure allows cables to be connected to internal devices. Additional cable glands are also provided on the enclosure for additional wiring.

Complete with Cable Glands and Wire Management Accessories - This enclosure includes 3 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray
Voltage / Max Load	120VAC / 10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	15.8 x 11.4 x 6.2 Inches (401 x 290 x 158 mm)
Inner Dimensions* (Height x Width x Depth)	9.8 x 8.0 x 3.8 Inches (248 x 203 x 97 mm)
Mounting Plate Material	0.06 in. (1.5mm) Aluminum
Weight	4.6 lbs. (2.0 kg)
Power Cord Length	5 Feet (1.5m)
Ratings	Meets or Exceeds NEMA 3R, 3RX and IP24
Flame Rating	Meets UL94-V0

*Interior dimensions represent maximum space available for equipment. See drawing for additional details.

Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2021 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.