



Features

- Removable Power Module with (2) 120VAC Power Outlets and 5 Ft. Power Cord
- Heavy Duty Continuous Seam Welded 18 Gauge AISI 304L Stainless Steel Construction
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Includes Blank Zinc Coated Galvanized Steel Equipment Mounting Plate
- Brushed Natural Finish
- Quarter-Turn Door Latch with Key
- Optional Keyed Lock Set Latch and Padlock Latch Available

Description

Construction and Features - This rugged IP66 rated enclosure features continuous seam welded 18 Gauge (1.2mm thick) AISI 304L stainless steel construction. The enclosure door is fully gasketed making this enclosure suitable for use indoors or outdoors. The door features reinforced hinges and a quarter-turn latch to secure the enclosure. Internal grounding studs are provided on both the door enclosure. Both the enclosure and door feature a brushed natural finish.

Removable Power Module - The NX161608A1C features a removable power module that attaches to the bottom of the enclosure. Constructed of rugged aluminum, this can be easily removed for servicing and is fully gasketed to ensure a proper seal. This power module features a pre-wired duplex 120VAC power outlet and a pre-wired 5 foot power cord, so no additional wiring is required.

Galvanized Steel Equipment Plate - This configuration consists of the stainless steel NEMA enclosure with hinged door and a 18 Gauge (1.2mm thick) zinc coated galvanized steel plate for mounting and securing equipment. The enclosure and plate can be drilled and modified by the installer to suit unique site requirements.

Optional Lockable Latches - For additional protection of internal equipment installed, two lockable latches are available. A keyed lock set which includes two keys as well as one that allows the enclosure to be securely locked via use of a padlock (not included). Both are direct replacements for the standard quarter-turn latches that come pre-installed in the enclosures.

Specifications

Material	Continuous Seam Welded 18 Gauge (1.2 mm) AISI 304L Stainless Steel
Color	Natural
Voltage / Max. Load	120VAC / 10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	15.8 x 15.8 x 7.9 Inches (400 x 400 x 200 mm)
Inner Dimensions* (Height x Width x Depth)	10.0 x 12.0 x 6.3 Inches (254 x 306 x 159 mm)
Equipment Mounting Plate Material	18 Gauge (1.2 mm) Zinc Coated Galvanized Steel
Equipment Mounting Plate Dimensions	14.3 x 13.8 In. (365 x 350 mm)
Weight	18.9 lbs. (8.5 kg)
Power Cord Length	5 Feet (1.5m)
Ratings*	Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66

*Notes:

- 1) Interior dimensions represent maximum space available for equipment.
- 2) Enclosure openings must be properly sealed with supplied plug to maintain NEMA Type 4, 4X / IP66 ratings.