

## SPLITTER

4-Way, 5-2300 MHz, Single Port Passing

### ELECTRICAL CHARACTERISTICS

FREQUENCY(MHz)	Transmission	Return Loss (dB)
5.00 MHz	-7.57 dB	-7.04 dB
96.00 MHz	-7.30 dB	-7.29 dB
188.60 MHz	-7.30 dB	-7.47 dB
280.40 MHz	-7.29 dB	-7.82 dB
372.20 MHz	-7.30 dB	-8.52 dB
464.00 MHz	-7.37 dB	-9.09 dB
555.80 MHz	-7.39 dB	-10.17 dB
647.60 MHz	-7.41 dB	-11.67 dB
739.40 MHz	-7.59 dB	-13.19 dB
831.20 MHz	-7.52 dB	-15.54 dB
920.00 MHz	-7.78 dB	-16.47 dB
1014.80 MHz	-7.94 dB	-17.53 dB
1106.60 MHz	-7.89 dB	-17.25 dB
1198.40 MHz	-8.24 dB	-16.19 dB
1290.20 MHz	-8.24 dB	-16.99 dB
1380.00 MHz	-8.50 dB	-16.65 dB
1473.80 MHz	-8.56 dB	-16.62 dB
1565.60 MHz	-8.25 dB	-17.94 dB
1657.40 MHz	-8.52 dB	-16.55 dB
1749.20 MHz	-8.53 dB	-14.95 dB
1841.00 MHz	-8.60 dB	-12.72 dB
1932.80 MHz	-8.86 dB	-10.43 dB
2024.60 MHz	-8.81 dB	-9.81 dB
2116.40 MHz	-9.18 dB	-9.04 dB
2208.20 MHz	-9.71 dB	-8.23 dB
2300.00 MHz	-9.65 dB	-8.42 dB

### MECHANICAL CHARACTERISTICS

Description	Material	Color
Zinc:	Zinc Alloy	Nickel Plating
Screw:	Iron	Nickel Plating
Cover Board:	Aluminum Board	Actual
Cap:	PVC	Blue
Screw:	Iron	Nickel Plating

