

Features:

- 1/3" 2 Megapixel progressive scan CMOS (ST-IP-MD3.6-2)
- 1/4" 1 Megapixel progressive scan CMOS (ST-IP-MD3.6-1)
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080), 25/30fps@720P
- Digital Wide Dynamic Range (DWDR)
- Day/Night, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3.6mm fixed lens
- DC12V, PoE
- For indoor use
- 2 Year Warranty

Description:

The Securitytronix ST-IP-MD3.6 series cameras are professional series 1 and 2 Megapixel IP cameras featuring either a 1/4" (1MP) or 1/3" (2MP) CMOS sensor and a fixed 3.6mm lens. This camera is perfect for indoor applications. Powering can be achieved through an external 12VDC power supply or via a separate PoE (Power over Ethernet) switch. The ST-IP-MD3.6 series are ONVIF Profile 'S' (Open Network Video Interface Forum) compliant. The ST-IP-MD3.6 series can be wall or ceiling mounted.



ST-IP-MD3.6-1 Specifications:

Camera	
Image Sensor	1/4" 1Megapixel progressive scan CMOS
Effective Pixels	1280(H)×720(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3(4)~1/10000
Min. Illumination	0.1Lux/F1.8(color), 0Lux/F1.8 (IR on)
S/N Ratio	More than 50dB

Camera Features

Day/Night	Auto(Electronic) / Color / B/W
Backlight Compensation	BLC /HLC /DWDR
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas

Lens

Focal Length	3.6mm
Max Aperture	F1.8(F2.0/F1.8)
Focus Control	Manual
Angle of View	H:55°(69.5°/37°)

Video

Compression	H.264 / MJPEG
Resolution	720P(1280×720)/ D1(704×576/704×480)/ CIF(352×288/352×240)
Frame Rate	Main Stream 720P(1 ~ 25/30fps) Sub Stream D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 56K ~ 8192Kbps

Network

Ethernet	RJ-45 (10/100Base-T)
Compatibility	ONVIF ,PSIA,CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone

General

Power Supply	DC12V, PoE(802.3af)
Power Consumption	<2W
Working Environment	-22°F~+/140°F, Less than 95%RH
Dimensions	4.3" × 2.12"
Weight	0.55 lbs.

Ordering Information:

ST-IP-MD3.6-1	IP Mini-Dome Camera, 1 Megapixel, Fixed 3.6mm Lens
ST-IP-MD3.6-2	IP Mini-Dome Camera, 2 Megapixel, Fixed 3.6mm Lens

ST-IP-MD3.6-2 Specifications:

Camera	
Image Sensor	1/3" 2 Megapixel progressive scan CMOS
Effective Pixels	2048(H)×1536(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3(4)~1/10000
Min. Illumination	0.1Lux/F1.2(color), 0Lux(IR on)
S/N Ratio	More than 50dB

Camera Features

Day/Night	Auto(Electronic) / Color / B/W
Backlight Compensation	BLC /HLC /DWDR
White Balance	Auto
Gain Control	Auto/Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas

Lens

Focal Length	3.6mm
Max Aperture	F1.8(F2.0/F1.8)
Focus Control	Manual
Angle of View	H:55°(69.5°/37°)

Video

Compression	H.264 / MJPEG
Resolution	1080P(1920×1080)/720P(1280×720)/ D1(704×576/704×480)/ CIF(352×288/352×240)
Frame Rate	Main Stream 1080P(1 ~ 25/30fps) Sub Stream D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 56K ~ 8192Kbps

Network

Ethernet	RJ-45 (10/100Base-T)
Compatibility	ONVIF ,PSIA,CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone

General

Power Supply	DC12V, PoE(802.3af)
Power Consumption	<2W
Working Environment	-22°F~+/140°F, Less than 95%RH
Dimensions	4.3" × 2.12"
Weight	0.55 lbs.

Package Includes:

- 1 IP Camera, 1Software CD
- 1 Operation manual
- 1 Mounting hardware