

SnapStak® Hanger for 1-1/4 in coaxial cable



Product Classification

| | |
|---------------------|------------|
| Brand | SnapStak® |
| Product Type | Hanger kit |

Dimensions

| | |
|-------------------------------------|----------------------|
| Nominal Size | 1-1/4 in |
| Compatible Diameter, maximum | 43.180 mm 1.700 in |
| Compatible Diameter, minimum | 37.592 mm 1.480 in |
| Height | 41.00 mm 1.61 in |
| Length | 81.00 mm 3.19 in |
| Width | 40.00 mm 1.57 in |

Electrical Specifications

| | |
|---------------------------|--------|
| DTF Effect | 0.1 dB |
| Return Loss Effect | 0.1 dB |

Environmental Specifications

| | |
|------------------------------|--------------------------------------|
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
|------------------------------|--------------------------------------|

General Specifications

| | |
|-----------------------------|---|
| Hanger Type | Snap-in hanger |
| Cables per Hanger | 1 |
| Color | Silver |
| Material Type | Stainless steel |
| Maximum Stack Height | 2 |
| Ordering Note | CommScope® standard product in Asia Pacific CommScope® standard product in Mexico, Central America, and South America CommScope® standard product in the United States and Canada |
| Package Quantity | 10 |

Mechanical Specifications

| | |
|--|----------------------------------|
| Corrosion Resistance, minimum with no degradation | =500 hours in salt spray chamber |
| Mounting | 3/4 in drilled cable ladder |
| Vibration Survival | =4 hours at resonant frequency |
| Environmental Strength Capability | Double cable weight |

Packed Dimensions

| | |
|------------------------|-------------------|
| Height | 22.0 cm 8.7 in |
| Length | 14.8 cm 5.8 in |
| Shipping Weight | 0.52 kg 1.15 lb |
| Width | 14.6 cm 5.7 in |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power